

Calculating Rotational Transform Following Field Lines

TODOROKI Jiro

National Institute for Fusion Science, Toki 509-5292, Japan

(Received 6 March 2003 / Accepted 20 March 2003)

A numerical method for calculating the rotational transform of the magnetic lines of force following the magnetic field line is described. The rotational transform is obtained by simultaneously solving differential equations.

Keywords:

rotational transform, magnetic coordinates, numerical calculation, field line tracing

Magnetic coordinates are commonly used in the study of plasma in toroidal magnetic confinement devices. To construct the magnetic coordinates, Boozer's algorithm [1] following the magnetic field line is widely used. In such calculations the rotational transform is the most important quantity of the magnetic surface. In this paper the efficient and accurate method calculating the rotational transform is described.

On the rational magnetic surface, magnetic lines of force are closed in n revolution around the long way and m revolution around the short way of the torus. The rotational transform is defined as

$$t = \frac{m}{n}. \quad (1)$$

On the irrational surface, the field line covers the surface without closing, and the rotational transform is defined as the ratio of the revolution of the infinite number

$$t \equiv \lim_{n \rightarrow \infty} \frac{m}{n} = \lim_{\phi \rightarrow \infty} \frac{\vartheta(\phi)}{\phi}, \quad (2)$$

where ϑ is the rotational angle in the poloidal direction corresponding to the toroidal rotation ϕ .

We consider the case in which the field line is traced in the cylindrical coordinates (r, z, ϕ) . If the azimuthal component of the magnetic field does not vanish, the equations for the magnetic field line can be written in the form

$$\frac{dr}{d\phi} = \frac{rB_r}{B_\phi}, \quad \frac{dz}{d\phi} = \frac{rB_z}{B_\phi}. \quad (3)$$

If we accept the definition of the rotational angle

$$\tan \vartheta = \frac{z(\phi) - z_A(\phi)}{r(\phi) - r_A(\phi)}, \quad (4)$$

where $(r_A(\phi), z_A(\phi))$ stands for a closed curve contained inside the magnetic surface, e.g., the magnetic axis, the rotational angle can be calculated by integrating the equation

$$\frac{d\vartheta}{d\phi} = \frac{(r - r_A)}{(r - r_A)^2 + (z - z_A)^2} \left\{ \frac{dz}{d\phi} - \frac{dz_A}{d\phi} \right\} - \frac{(z - z_A)}{(r - r_A)^2 + (z - z_A)^2} \left\{ \frac{dr}{d\phi} - \frac{dr_A}{d\phi} \right\}. \quad (5)$$

This equation is solved simultaneously with the equations for the field line.

On the magnetic surface, the angle ϑ is expressed in terms of the magnetic coordinates θ and ϕ as

$$\vartheta = \theta + \sum_{m,n} c_{m,n} \exp(i[m\theta - n\phi]). \quad (6)$$

We assume that the angle variable θ is chosen so that the magnetic field line is straight in $\theta - \phi$ plane. Since $\theta = t\phi$ on a field line, the rotational angle behaves along the field line as

$$\vartheta = t\phi + \sum_{m,n} c_{m,n} \exp(i\omega_{m,n}\phi), \quad (7)$$

where $\omega_{m,n} \equiv mt - n$.

If we apply definition (2) naively, we obtain the very rough evaluation formula

author's e-mail: todoroki@nifs.ac.jp

$$\iota = \frac{\vartheta_N}{\phi_N} + O\left(\frac{1}{\phi_N}\right). \quad (8)$$

In ref. [2] the author used the evaluation

$$\iota = \frac{2}{\phi_N^2} \sum_{j=1}^N \vartheta_j + O\left(\frac{1}{\phi_N^2}\right), \quad (9)$$

which is more precise than eq. (8). Reiman and Greenside [3] described an evaluation based on the least square fit of the numerous data with eq. (7). They introduce the quantity

$$G(\iota, c_{m,n}) = \sum_{j=1}^N |F_j|^2, \quad (10)$$

where

$$F_j \equiv \vartheta_j - \iota \phi_j - \sum_{m,n} c_{m,n} \exp(i\omega_{m,n} \phi_j). \quad (11)$$

The function G is minimized with respect to ι as well as Fourier coefficients $c_{m,n}$. The minimization is performed by repeatedly evaluating coefficients $c_{m,n}$ for a given value of ι .

One common feature of these two methods is to evaluate the rotational transform after completion of the integration of the field line. Here we propose a simpler method for evaluating rotational transform in the course of integrating the equations of the field line.

Differentiating eq. (7) with respect to ϕ , we obtain

$$\frac{d\vartheta}{d\phi} = \iota + i \sum_{m,n} c_{m,n} \omega_{m,n} \exp(i\omega_{m,n} \phi). \quad (12)$$

The rotational transform ι is the DC part of the function in the right hand side of eq. (12). Hence by posing the Gaussian window in order to eliminate the end effects, we can calculate using the relation

$$\iota \equiv \frac{\alpha}{\sqrt{\pi}} \int_{-\phi_{\max}}^{\phi_{\max}} \frac{d\vartheta}{d\phi} \exp\left(-\frac{\alpha^2 \phi^2}{\phi_{\max}^2}\right) \frac{d\phi}{\phi_{\max}}, \quad (13)$$

with α a number chosen to achieve a desired level of accuracy. In practice, α is about 3. In the actual calculation, we consider the following differential equation

$$\frac{dw}{d\phi} = \frac{d\vartheta}{d\phi} \frac{\alpha}{\sqrt{\pi}} \exp\left(-\frac{\alpha^2 \phi^2}{\phi_{\max}^2}\right) \quad (14)$$

with the initial condition $w(0) = 0$. The equation is solved simultaneously with the other equations following the magnetic line of force. The equations for the magnetic axis are also solved simultaneously, if required. After the integration is finished, the rotational transform is obtained by the formula

$$\iota = \frac{w(\phi_{\max}) - w(-\phi_{\max})}{\phi_{\max}}. \quad (15)$$

The same technique can be used to obtain the other surface quantities, such as the specific volume

$$U \equiv \frac{\alpha}{\sqrt{\pi}} \int_{-\phi_{\max}}^{\phi_{\max}} \frac{r}{B_\phi} \exp\left(-\frac{\alpha^2 \phi^2}{\phi_{\max}^2}\right) \frac{d\phi}{\phi_{\max}}. \quad (16)$$

Finally, it is worth noting that the method described in this paper has no difficulty concerning the rational surface.

[1] A. Boozer, Phys. Fluids **25**, 520 (1982).
 [2] J. Todoroki, J. Phys. Soc. Jpn. **58**, 3979 (1989).
 [3] A. Reiman and H. Greenside, Comput. Phys. Commun. **43**, 157 (1986).